

8 7 6 5 4 3 2 1

REV:	DESCRIPTION	BY	DATE
V1.0	New issue		2016-05-08

D
C
B
A

D
C
B
A

PIN DESCRIPTION

NO.	SYMBOL
1	LED+
2	LED+
3	LED-
4	LED-
5	COM
6	VDD
7	AVDD
8	AVDD
9	LED
10	LED
11	LED
12	LED
13	LED
14	LED
15	LED
16	LED
17	LED
18	LED
19	LED
20	LED
21	LED
22	LED
23	LED
24	LED
25	LED
26	LED
27	LED
28	LED
29	LED
30	LED
31	LED
32	LED
33	LED
34	LED
35	LED
36	LED
37	LED
38	LED
39	LED
40	LED
41	LED
42	LED
43	LED
44	LED
45	LED
46	LED
47	LED
48	LED
49	LED
50	LED

Display Type	TFT
	NEGATIVE
	TRANSMISSIVE
Viewing Angle	6°OCLOCK
VDD	3.0V
Operation Temperature	-20°C TO +70°C
Storage Temperature	-30°C TO +80°C
Backlight Color	WHITE
Interface	--
Drive IC	
All radii without dimension	
Unspecified tolerance is	±0.2
ROHS request	Yes

		SINDA DISPLAY TECHNOLOGY CO., LTD.	
SHEET: 1 of 1		MODEL NUMBER :	VERSION: 1.0
APPROVALS		DATE	UNITS: MM
DWN	SD-03	2016-05-08	GENERAL TOL: ± 0.2
CHK			DO NOT SCALE THIS DRAWING.
APP	SD-11	2016-05-08	
www.sindadisplay.com			SCALE: 1:1

8 7 6 5 4 3 2 1