



<https://www.wago.com/211-501/000-002>



Color:  yellow

Similar to illustration

Technical data	
Suitable	for wire cross-section 0.75 ... 1 mm²
Marking method	Thermal transfer
Delivery form	Roll
Delivery form configuration	20 m/roll
Printing device	Smart Printer (thermal transfer printer)

Physical data	
Depth	0.185 mm

Mechanical Data	
Mounting type	Sliding on
Shrink rate	2:1
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material Data	
Color	yellow
Material	Polyolefin
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	199.6 g
Fire load	0 MJ



Environmental requirements	
Surrounding air temperature (storage)	+10 ... +25 °C
Ambient temperature (operation)	-55 ... +125 °C
Relative humidity	45 ... 55 %

Commercial data	
eCl@ss 10.0	27-40-04-01
eCl@ss 9.0	27-40-04-01
ETIM 8.0	EC001530
ETIM 7.0	EC001530
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DK
GTIN	4055143370233
Customs tariff number	85472000900