



JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

JSCJ TO-252-2L Plastic-Encapsulate Transistors


MJD2955 TRANSISTOR (PNP)

FEATURES


- Designed for General Purpose Amplifier and Low Speed Switching Applications
- Electrically Similar to MJD3055
- DC Current Gain Specified to 10 Amperes

TO-252-2L

- 1.BASE
2.COLLECTOR
3.EMITTER




MARKING



MJD2955=Device code
Solid dot=Green moldinn compound device,
if none,the normal device
XXXX=Code

Equivalent Circuit



MAXIMUM RATINGS (T_a=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V _{CBO}	Collector-Base Voltage	-70	V
V _{CEO}	Collector-Emitter Voltage	-60	V
V _{EBO}	Emitter-Base Voltage	-5	V
I _C	Collector Current -Continuous	-10	A
I _{CM}	Peak Pulse Current	-20	A
P _C ②	Collector Power Dissipation	1.25	W
R _{θJC} ①	Thermal Resistance from Junction to Case	5.0	°C/W
R _{θJA} ②	Thermal Resistance from Junction to Ambient	100	°C/W
T _J , T _{stg}	Operation Junction and Storage Temperature Range	-55~+150	°C

MOSFET ELECTRICAL CHARACTERISTICS

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=-1\text{mA}, I_E=0$	-70			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=-200\text{mA}, I_B=0$	-60			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=-1\text{mA}, I_C=0$	-5			V
Collector cut-off current	I_{CBO}	$V_{CB}=-70\text{V}, I_E=0$			-0.02	mA
	I_{CEO}	$V_{CB}=-30\text{V}, I_B=0$			-50	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=-5\text{V}, I_C=0$			-0.5	mA
DC current gain	$h_{FE(1)}$	$V_{CE}=-4\text{V}, I_C=-4\text{A}$	20		100	
	$h_{FE(2)}$	$V_{CE}=-4\text{V}, I_C=-10\text{A}$	5			
Collector-emitter saturation voltage	$V_{CE(sat)(1)}$	$I_C=-4\text{A}, I_B=-0.4\text{A}$			-1.1	V
	$V_{CE(sat)(2)}$	$I_C=-10\text{A}, I_B=-3.3\text{A}$			-8	V
Base-emitter voltage	V_{BE}	$V_{CE}=-4\text{V}, I_C=-4\text{A}$			-1.8	V
Transition frequency	f_T	$V_{CE}=-10\text{V}, I_C=-0.5\text{A}, f=500\text{KHz}$	2			MHz



Notes:

1. $T_C=25^{\circ}\text{C}$.


2. Device mounted on 1 in² FR-4 board with 2oz. single-sided Copper, in a still air environment with $T_A=25^{\circ}\text{C}$.

Typical Characteristics






TO-252-2L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.770	0.025	0.030
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.382	0.406
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250 REF.		0.207 REF.	

TO-252-2L Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.


TO-252 Embossed Carrier Tape




Packaging Description:
TO-252 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 25,00 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
TO-252	6.90	10.50	2.70	Ø1.55	1.75	7.50	4.00	8.00	2.00	16.00

TO-252 Tape Leader and Trailer



TO-252 Reel



Dimensions are in millimeter						
Reel Option	D	D1	D2	W1	W2	I
13"Dia	330.00	100.00	Ø21.00	16.40	21.00	Ø13.00

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
2,500 pcs	13inch	2,500 pcs	340×336×29	25,000 pcs	353×346×365	