

ABB430R7W

# Panel mounted socket

## 2CMA100450R1000



IEC Receptacle 30A 3P4W 3phase 480V Clock Position Of  
Grounding Contact 7 hour Color code Red, UL/CSA approved  
and CE compliant

## GENERAL

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| Product Name        | Panel mounted socket                                                           |
| Product ID          | 2CMA100450R1000                                                                |
| Function            | Receptacle                                                                     |
| EAN                 | 739269043                                                                      |
| Catalog Description | IEC Receptacle 30A<br>3P4W 3phase 480V,<br>UL/CSA approved and<br>CE compliant |
| Country of Origin   | Czech Republic (CZ)                                                            |
| E-Number Finland    |                                                                                |
| E-Number Norway     |                                                                                |
| E-Number Sweden     |                                                                                |
| Standards           | UL 1682, 1686 / CSA<br>C22.2 No. 182.1-13                                      |
| RoHS Status         | Following EU Directive<br>2011/65/EU                                           |

## DIMENSIONS

|                    |                |
|--------------------|----------------|
| Product Net Width  | 102 millimetre |
| Product Net Height | 110 millimetre |
| Product Net Length | 110 millimetre |
| Product Net Depth  | 110 millimetre |
| Product Net Weight | 0.21 kilogram  |

## TECHNICAL

|                      |                          |
|----------------------|--------------------------|
| Product Main Type    | TRAU                     |
| Color                | Red                      |
| Number of Poles      | 4                        |
| Clock Position       | 7Hour                    |
| Rated Current        | 30 ampere                |
| Rated Voltage        | 480 ... 500 volt         |
| Frequency            | 50 hertz 60 hertz        |
| Degree of Protection | IP67 IP69                |
| Cable Cross-Section  | 2.5...10 mm <sup>2</sup> |
| Housing Material     | Thermoplastic (PBT)      |
| Plug Angle           | Angled                   |
| Product Group        | Tough&Safe               |

## PACKAGING

|                      |                |
|----------------------|----------------|
| Package Width        | 110 millimetre |
| Package Height       | 110 millimetre |
| Package Gross Weight | 0.21 kilogram  |
| Package Length       | 110 millimetre |
| Package Units        | box 1 piece    |