




JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

PDFNWB5×6-8L Plastic-Encapsulate MOSFETS

CJAC75SN10 N-Channel Power MOSFET

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
100V	8.0mΩ@10V	75A
	10.5mΩ@4.5V	



DESCRIPTION

The CJAC75SN10 uses SGT technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications .


FEATURES

- High Power and current handing capability
- Load switch
- High density cell design for ultra low $R_{DS(ON)}$
- Lead free product is acquired
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation

APPLICATIONS


- SMPS and general purpose applications
- Hard switched and high frequency circuits
- Uninterruptible Power Supply
- Power management

MARKING



CJAC75SN10= Part No.
Solid dot=Pin1 indicator.
XX=Code.

EQUIVALENT CIRCUIT



ABSOLUTE MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D ①	75	A
Pulsed Drain Current	I_{DM} ②	260	A
Single Pulsed Avalanche Energy	E_{AS} ③	150	mJ
Maximum Power Dissipation	P_D ①	100	W
Thermal Resistance from Junction to Case	$R_{\theta JC}$ ①	1.25	$^{\circ}\text{C/W}$
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$ ⑥	62.5	$^{\circ}\text{C/W}$
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55~+150	$^{\circ}\text{C}$

MOSFET ELECTRICAL CHARACTERISTICS







$T_a=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Off characteristics							
Drain-source breakdown voltage	V _{(BR) DSS}	V _{GS} = 0V, I _D =250uA		100			V
Zero gate voltage drain current	I _{DSS}	V _{DS} =80V,	T _J =25 ℃			1.0	μA
		V _{GS} =0V	T _J =125 ℃			100	
Gate-body leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V				±100	nA
On characteristics ④							
Gate-threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA		1.0	1.75	2.5	V
Static drain-source on-sate resistance	R _{DS(on)}	V _{GS} =10V, I _D =10A			8.0	10	mΩ
		V _{GS} =4.5V, I _D =10A			10.5	16	mΩ
Dynamic characteristics ④ ⑤							
Input capacitance	C _{iss}	V _{DS} =50V,V _{GS} =0V, f =100KHz			1850	3700	pF
Output capacitance	C _{oss}				356	712	
Reverse transfer capacitance	C _{rss}				5.3	10.6	
Gate resistance	R _g	f =1MHz			2.1		Ω
Switching characteristics ④ ⑤							
Total gate charge	Q _g	V _{GS} =10V, V _{DS} =50V, I _D =20A			28	57	nC
Gate-source charge	Q _{gs}				4.1	8.2	
Gate-drain charge	Q _{gd}				6.2	12	
Turn-on delay time	t _{d(on)}	V _{DS} =50V,I _D =20A , V _{GS} =10V,R _G =10Ω			8	16	ns
Turn-on rise time	t _r				5.2	11	
Turn-off delay time	t _{d(off)}				44.8	90	
Turn-off fall time	t _f				5.6	13	
Drain-Source Diode Characteristics							
Drain-source diode forward voltage	V _{SD} ④	V _{GS} =0V, I _S =20A				1.2	V
Continuous drain-source diode forward current	I _S ①					75	A
Pulsed drain-source diode forward current	I _{SM} ②					260	A

Notes:


1. $T_C = 25^{\circ}\text{C}$ Limited only by maximum temperature allowed.
2. $P_{W} \leq 10\mu s$, Duty cycle $\leq 1\%$.
3. EAS condition: $V_{DD} = 50V, V_{GS} = 10V, L = 0.1\text{mH}, R_g = 25\Omega$ Starting $T_J = 25^{\circ}\text{C}$.
4. Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
5. Guaranteed by design, not subject to production.
6. The value of $R_{\theta JA}$ is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_a = 25^{\circ}\text{C}$.

Typical Characteristics




Typical Characteristics


Capacitances




Gate Charge



Maximum Forward Biased Safe Operating Area




PDFNWB5×6-8L PACKAGE OUTLINE DIMENSIONS



Top View
[顶视图]



Bottom View
[背视图]




Side View
[侧视图]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.90	1.10	0.035	0.043
A1	0.25 REF.		0.010 REF.	
D	4.90	5.10	0.193	0.201
D1	4.80	5.00	0.189	0.197
D2	3.90	4.10	0.154	0.161
E	5.90	6.10	0.232	0.240
E1	5.65	5.85	0.222	0.230
E2	3.35	3.65	0.132	0.144
k	1.20	1.50	0.047	0.059
b	0.20	0.45	0.008	0.018
e	1.27 BSC		0.050 BSC	
L	0.55	0.75	0.022	0.030
H	0.45	0.75	0.018	0.030

- Notes:
- 1 Dimensions exclusive of mold gate burrs.
 - 2 Dimensions exclusive of mold flash and cutting burrs.

PDFNWB5×6-8L Suggested Pad Layout



- Notes:
- 1 Controlling dimension: in millimeters.
 - 2 General tolerance:±0.05mm.
 - 3 The pad layout is for reference purpose only.

NOTICE

JSCJ reservesthe right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein.JSCJ does not assume any liability arising out of the application or use of any product described herein.

PDFNWB5×6 Tape and Reel

PDFNWB5×6-8L Embossed Carrier Tape




Packaging Description:
PDFNWB5×6-8L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 5,000 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
PDFNWB5×6-8L	6.30	5.30	1.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

PDFNWB5×6-8L Tape Leader and Trailer



PDFNWB5×6-8L Reel



Dimensions are in millimeter						
Reel Option	D	D1	D2	G	W1	W2
13"Dia	Ø330.00	100.00	13.00	1.90	17.60	12.40

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
5,000 pcs	13 inch	5,000 pcs	340×336×29	50,000 pcs	353×346×365