



**POWER MOS 7® FREDFET**

Power MOS 7® is a new generation of low loss, high voltage, N-Channel enhancement mode power MOSFETS. Both conduction and switching losses are addressed with Power MOS 7® by significantly lowering  $R_{DS(ON)}$  and  $Q_g$ . Power MOS 7® combines lower conduction and switching losses along with exceptionally fast switching speeds inherent with APT's patented metal gate structure.



- Lower Input Capacitance
- Lower Miller Capacitance
- Lower Gate Charge,  $Q_g$
- Increased Power Dissipation
- Easier To Drive
- TO-247 or Surface Mount D<sup>3</sup>PAK Package
- **FAST RECOVERY BODY DIODE**


**MAXIMUM RATINGS**

All Ratings:  $T_C = 25^\circ\text{C}$  unless otherwise specified.

| Symbol         | Parameter                                                      | APT1001R6BFLL_SFLL | UNIT                |
|----------------|----------------------------------------------------------------|--------------------|---------------------|
| $V_{DSS}$      | Drain-Source Voltage                                           | 1000               | Volts               |
| $I_D$          | Continuous Drain Current @ $T_C = 25^\circ\text{C}$            | 8                  | Amps                |
| $I_{DM}$       | Pulsed Drain Current <sup>①</sup>                              | 32                 |                     |
| $V_{GS}$       | Gate-Source Voltage Continuous                                 | $\pm 30$           | Volts               |
| $V_{GSM}$      | Gate-Source Voltage Transient                                  | $\pm 40$           |                     |
| $P_D$          | Total Power Dissipation @ $T_C = 25^\circ\text{C}$             | 266                | Watts               |
|                | Linear Derating Factor                                         | 2.13               | W/ $^\circ\text{C}$ |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range               | -55 to 150         | $^\circ\text{C}$    |
| $T_L$          | Lead Temperature: 0.063" from Case for 10 Sec.                 | 300                |                     |
| $I_{AR}$       | Avalanche Current <sup>①</sup> (Repetitive and Non-Repetitive) | 4                  | Amps                |
| $E_{AR}$       | Repetitive Avalanche Energy <sup>①</sup>                       | 16                 | mJ                  |
| $E_{AS}$       | Single Pulse Avalanche Energy <sup>④</sup>                     | 425                |                     |

**STATIC ELECTRICAL CHARACTERISTICS**

| Symbol       | Characteristic / Test Conditions                                                          | MIN  | TYP | MAX       | UNIT    |
|--------------|-------------------------------------------------------------------------------------------|------|-----|-----------|---------|
| $BV_{DSS}$   | Drain-Source Breakdown Voltage ( $V_{GS} = 0V, I_D = 250\mu A$ )                          | 1000 |     |           | Volts   |
| $R_{DS(on)}$ | Drain-Source On-State Resistance <sup>②</sup> ( $V_{GS} = 10V, I_D = 4A$ )                |      |     | 1.600     | Ohms    |
| $I_{DSS}$    | Zero Gate Voltage Drain Current ( $V_{DS} = 1000V, V_{GS} = 0V$ )                         |      |     | 250       | $\mu A$ |
|              | Zero Gate Voltage Drain Current ( $V_{DS} = 800V, V_{GS} = 0V, T_C = 125^\circ\text{C}$ ) |      |     | 1000      |         |
| $I_{GSS}$    | Gate-Source Leakage Current ( $V_{GS} = \pm 30V, V_{DS} = 0V$ )                           |      |     | $\pm 100$ | nA      |
| $V_{GS(th)}$ | Gate Threshold Voltage ( $V_{DS} = V_{GS}, I_D = 1mA$ )                                   | 3    |     | 5         | Volts   |



**CAUTION:** These Devices are Sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

APT Website - <http://www.advancedpower.com>

# DYNAMIC CHARACTERISTICS

APT1001R6BFL S\_FLL

| Symbol       | Characteristic               | Test Conditions                                                                                                 | MIN | TYP  | MAX | UNIT    |
|--------------|------------------------------|-----------------------------------------------------------------------------------------------------------------|-----|------|-----|---------|
| $C_{iss}$    | Input Capacitance            | $V_{GS} = 0V$<br>$V_{DS} = 25V$<br>$f = 1 \text{ MHz}$                                                          |     | 1320 |     | pF      |
| $C_{oss}$    | Output Capacitance           |                                                                                                                 |     | 230  |     |         |
| $C_{rss}$    | Reverse Transfer Capacitance |                                                                                                                 |     | 42   |     |         |
| $Q_g$        | Total Gate Charge ③          | $V_{GS} = 10V$<br>$V_{DD} = 500V$<br>$I_D = 8A @ 25^\circ C$                                                    |     | 55   |     | nC      |
| $Q_{gs}$     | Gate-Source Charge           |                                                                                                                 |     | 7    |     |         |
| $Q_{gd}$     | Gate-Drain ("Miller") Charge |                                                                                                                 |     | 35   |     |         |
| $t_{d(on)}$  | Turn-on Delay Time           | <b>RESISTIVE SWITCHING</b><br>$V_{GS} = 15V$<br>$V_{DD} = 500V$<br>$I_D = 8A @ 25^\circ C$<br>$R_G = 0.6\Omega$ |     | 18   |     | ns      |
| $t_r$        | Rise Time                    |                                                                                                                 |     | 18   |     |         |
| $t_{d(off)}$ | Turn-off Delay Time          |                                                                                                                 |     | 32   |     |         |
| $t_f$        | Fall Time                    |                                                                                                                 |     | 19   |     |         |
| $E_{on}$     | Turn-on Switching Energy ⑥   | <b>INDUCTIVE SWITCHING @ 25°C</b><br>$V_{DD} = 667V$ $V_{GS} = 15V$<br>$I_D = 8A$ , $R_G = 5\Omega$             |     | 210  |     | $\mu J$ |
| $E_{off}$    | Turn-off Switching Energy    |                                                                                                                 |     | 40   |     |         |
| $E_{on}$     | Turn-on Switching Energy ⑥   | <b>INDUCTIVE SWITCHING @ 125°C</b><br>$V_{DD} = 667V$ $V_{GS} = 15V$<br>$I_D = 8A$ , $R_G = 5\Omega$            |     | 450  |     |         |
| $E_{off}$    | Turn-off Switching Energy    |                                                                                                                 |     | 50   |     |         |

# SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

| Symbol    | Characteristic / Test Conditions                                  | MIN                 | TYP  | MAX | UNIT    |
|-----------|-------------------------------------------------------------------|---------------------|------|-----|---------|
| $I_S$     | Continuous Source Current (Body Diode)                            |                     |      | 8   | Amps    |
| $I_{SM}$  | Pulsed Source Current ① (Body Diode)                              |                     |      | 32  |         |
| $V_{SD}$  | Diode Forward Voltage ② ( $V_{GS} = 0V$ , $I_S = -8A$ )           |                     |      | 1.3 | Volts   |
| $dv/dt$   | Peak Diode Recovery $dv/dt$ ⑤                                     |                     |      | 18  | V/ns    |
| $t_{rr}$  | Reverse Recovery Time<br>( $I_S = -8A$ , $di/dt = 100A/\mu s$ )   | $T_j = 25^\circ C$  |      | 250 | ns      |
|           |                                                                   | $T_j = 125^\circ C$ |      | 515 |         |
| $Q_{rr}$  | Reverse Recovery Charge<br>( $I_S = -8A$ , $di/dt = 100A/\mu s$ ) | $T_j = 25^\circ C$  | 0.50 |     | $\mu C$ |
|           |                                                                   | $T_j = 125^\circ C$ | 1.1  |     |         |
| $I_{RRM}$ | Peak Recovery Current<br>( $I_S = -8A$ , $di/dt = 100A/\mu s$ )   | $T_j = 25^\circ C$  | 8.3  |     | Amps    |
|           |                                                                   | $T_j = 125^\circ C$ | 11.5 |     |         |

# THERMAL CHARACTERISTICS

| Symbol          | Characteristic      | MIN | TYP | MAX  | UNIT         |
|-----------------|---------------------|-----|-----|------|--------------|
| $R_{\theta JC}$ | Junction to Case    |     |     | 0.47 | $^\circ C/W$ |
| $R_{\theta JA}$ | Junction to Ambient |     |     | 40   |              |

① Repetitive Rating: Pulse width limited by maximum junction temperature

② Pulse Test: Pulse width < 380  $\mu s$ , Duty Cycle < 2%

③ See MIL-STD-750 Method 3471

④ Starting  $T_j = +25^\circ C$ ,  $L = 13.28mH$ ,  $R_G = 25\Omega$ , Peak  $I_L = 8A$

⑤  $dv/dt$  numbers reflect the limitations of the test circuit rather than the device itself.  $I_S \leq I_D - 8A$   $di/dt \leq 700A/\mu s$   $V_R \leq 1000$   $T_j \leq 150^\circ C$

⑥  $E_{on}$  includes diode reverse recovery. See figures 18, 20.

APT Reserves the right to change, without notice, the specifications and information contained herein.




FIGURE 1, MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs PULSE DURATION

## Typical Performance Curves




FIGURE2, TRANSIENT THERMAL IMPEDANCE MODEL




FIGURE 4, TRANSFER CHARACTERISTICS




FIGURE6, MAXIMUM DRAIN CURRENT vs CASE TEMPERATURE




FIGURE8, ON-RESISTANCE vs. TEMPERATURE




FIGURE3, LOW VOLTAGE OUTPUT CHARACTERISTICS




FIGURE 5,  $R_{DS}(\text{ON})$  vs DRAIN CURRENT




FIGURE7, BREAKDOWN VOLTAGE vs TEMPERATURE




FIGURE9, THRESHOLD VOLTAGE vs TEMPERATURE




FIGURE 10, MAXIMUM SAFE OPERATING AREA




FIGURE 12, GATE CHARGE vs GATE-TO-SOURCE VOLTAGE




FIGURE 14, DELAY TIMES vs CURRENT




FIGURE 16, SWITCHING ENERGY vs CURRENT




FIGURE 11, CAPACITANCE vs DRAIN-TO-SOURCE VOLTAGE




FIGURE 13, SOURCE-DRAIN DIODE FORWARD VOLTAGE




FIGURE 15, RISE AND FALL TIMES vs CURRENT




FIGURE 17, SWITCHING ENERGY vs. GATE RESISTANCE




Figure 18, Turn-on Switching Waveforms and Definitions




Figure 19, Turn-off Switching Waveforms and Definitions






Figure 20, Inductive Switching Test Circuit

## TO-247 Package Outline



## D<sup>3</sup>PAK Package Outline



APT's products are covered by one or more of U.S. patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522

5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents. US and Foreign patents pending. All Rights Reserved.