




JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

TO-252-2L Plastic-Encapsulate MOSFETS

CJU4410 N-Channel 30-V(D-S) MOSFET

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
30V	8.0mΩ@10V	7.5A
	11.5mΩ@4.5V	

TO-252-2L




FEATURE

TrenchFET Power MOSFET

APPLICATIONS


- Load Switch
- Battery Switch

MARKING



U4410= Device code
Solid dot = Green molding compound device,
if none, the normal device
XXXX=Code

EQUIVALENT CIRCUIT



Maximum ratings ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current	I_D	7.5	A
Power Dissipation (note 1, $T_a=25^{\circ}\text{C}$)	P_D	1	W
Maximum Power Dissipation (note 2, $T_c=25^{\circ}\text{C}$)		15	
Thermal Resistance from Junction to Ambient ($t \leq 10\text{S}$)	$R_{\theta JA}$	125	$^{\circ}\text{C/W}$
Operating Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-55 ~ +150	

MOSFET ELECTRICAL CHARACTERISTICS







$T_a=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	30			V
Gate-source threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	1	1.5	3	
Gate-source leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$			± 100	nA
Zero gate voltage drain current	I_{DSS}	$V_{DS} = 30V, V_{GS} = 0V$			1	μA
Drain-source on-state resistance (note 3)	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 10A$		8	13.5	m Ω
		$V_{GS} = 4.5V, I_D = 5A$		11.5	20	
Forward transconductance (note 3)	g_{fs}	$V_{DS} = 15V, I_D = 5A$		8		S
Body diode voltage (note 3)	V_{SD}	$I_S = 2.3A, V_{GS} = 0$			1.1	V
Dynamic (note 4)						
Turn-on delay time	$t_{d(on)}$	$V_{DD} = 25V,$ $R_L = 25\Omega, I_D = 1A,$ $V_{GEN} = 10V, R_G = 6\Omega$			15	ns
Rise time	t_r				15	
Turn-off delay time	$t_{d(off)}$				60	
Fall time	t_f				25	
Gate Resistance	R_g	$f = 1MHz$	0.5		2.7	Ω


Notes :

1. This test is performed with no heat sink at $T_a=25^{\circ}\text{C}$.
2. This test is performed with infinite heat sink at $T_c=25^{\circ}\text{C}$.
3. Pulse Test : Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$.
4. Guaranteed by design, not subject to production testing.

Typical Characteristics




TO-252-2L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.770	0.025	0.030
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.382	0.406
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250 REF.		0.207 REF.	

TO-252-2L Suggested Pad Layout



Note:


1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

TO-252-2L Tape and Reel

TO-252 Embossed Carrier Tape




Packaging Description:


TO-252 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 25,00 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
TO-252	6.90	10.50	2.70	Ø1.55	1.75	7.50	4.00	8.00	2.00	16.00

TO-252 Tape Leader and Trailer



TO-252 Reel



Dimensions are in millimeter						
Reel Option	D	D1	D2	W1	W2	I
13"Dia	330.00	100.00	Ø21.00	16.40	21.00	Ø13.00

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
2,500 pcs	13inch	2,500 pcs	340×336×29	25,000 pcs	353×346×365	