

SOT-323 Plastic-Encapsulate Transistors

S9018W TRANSISTOR (NPN)


FEATURES

- Small Surface Mount Package

MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	30	V
V_{CEO}	Collector-Emitter Voltage	15	V
V_{EBO}	Emitter-Base Voltage	5	V
I_{C}	Collector Current	50	mA
P_{C}	Collector Power Dissipation	200	mW
R_{QJA}	Thermal Resistance From Junction To Ambient	625	$^{\circ}\text{C/W}$
$T_{\text{J}}, T_{\text{stg}}$	Operation Junction and Storage Temperature Range	-55~+150	$^{\circ}\text{C}$

SOT - 323



1. BASE
2. EMITTER
3. COLLECTOR


ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(\text{BR})\text{CBO}}$	$I_{\text{C}}=100\mu\text{A}, I_{\text{E}}=0$	30			V
Collector-emitter breakdown voltage	$V_{(\text{BR})\text{CEO}}$	$I_{\text{C}}=1\text{mA}, I_{\text{B}}=0$	15			V
Emitter-base breakdown voltage	$V_{(\text{BR})\text{EBO}}$	$I_{\text{E}}=100\mu\text{A}, I_{\text{C}}=0$	5			V
Collector cut-off current	I_{CBO}	$V_{\text{CB}}=12\text{V}, I_{\text{E}}=0$			50	nA
Collector cut-off current	I_{CEO}	$V_{\text{CE}}=12\text{V}, I_{\text{B}}=0$			100	nA
Emitter cut-off current	I_{EBO}	$V_{\text{EB}}=3\text{V}, I_{\text{C}}=0$			100	nA
DC current gain	h_{FE}	$V_{\text{CE}}=5\text{V}, I_{\text{C}}=1\text{mA}$	100		200	
Collector-emitter saturation voltage	$V_{\text{CE(sat)}}$	$I_{\text{C}}=10\text{mA}, I_{\text{B}}=1\text{mA}$			0.5	V
Base-emitter saturation voltage	$V_{\text{BE(sat)}}$	$I_{\text{C}}=10\text{mA}, I_{\text{B}}=1\text{mA}$			1.4	V
Transition frequency	f_{T}	$V_{\text{CE}}=5\text{V}, I_{\text{C}}=5\text{mA}, f=400\text{MHz}$	600			MHz
Collector output capacitance	C_{ob}	$V_{\text{CB}}=10\text{V}, I_{\text{E}}=0, f=1\text{MHz}$			2	pF

CLASSIFICATION OF h_{FE}


RANK	H
RANGE	100 - 200
MARKING	J8

SOT-323 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
theta	0°	8°	0°	8°

SOT-323 Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.05 mm.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.


SOT-323 Embossed Carrier Tape




Packaging Description:
SOT-323 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-323	2.25	2.55	1.19	Ø1.55	1.75	3.50	4.00	4.00	2.00	8.00

SOT-323 Tape Leader and Trailer



SOT-323 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	