


**TO-252-2L Plastic-Encapsulate MOSFETS****CJU50P06 P-Channel Power MOSFET**

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
-60V	25mΩ@-10V	-50A

GENERAL DESCRIPTION

The CJU50P06 uses advanced trench technology and design to provide excellent $R_{DS(on)}$ with low gate charge. It can be used in a wide variety of applications.

TO-252-2L


1. GATE
2. DRAIN
3. SOURCE

FEATURE


- Advanced trench process technology
- Reliable and rugged
- High density cell design for ultra low On-Resistance

APPLICATION

- Power management in notebook computer
- Portable equipment and battery powered systems

MARKING

U50P06 = Device code
Solid dot = Green molding compound device,
if none, the normal device
XXXX = Code

EQUIVALENT CIRCUIT**MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)**

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	I_D ①	-50	A
Pulsed Drain Current	I_{DM} ②	-200	A
Single Pulsed Avalanche Energy	E_{AS} ③	196	mJ
Power Dissipation	P_D ①	75	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$ ⑥	100	$^{\circ}\text{C/W}$
Thermal Resistance from Junction to Case	$R_{\theta JC}$ ①	1.66	$^{\circ}\text{C/W}$
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55~+150	$^{\circ}\text{C}$

MOSFET ELECTRICAL CHARACTERISTICS

$T_a=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Off characteristics							
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$		-60			V
Zero gate voltage drain current	I_{DSS}	$V_{DS}=-48V,$ $V_{GS}=0V$	$T_J=25^{\circ}C$			1.0	μA
			$T_J=125^{\circ}C$			100	
Gate-body leakage current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$				± 100	nA
On characteristics ④							
Gate-threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$		-1.0	-2.2	-3.0	V
Static drain-source on-sate resistance	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-20A$			25	30	mΩ
Dynamic characteristics ⑤							
Input capacitance	C_{iss}	$V_{DS}=-25V, V_{GS}=0V,$ $f=1MHz$			4500	7500	pF
Output capacitance	C_{oss}				705	980	
Reverse transfer capacitance	C_{rss}				515	760	
Gate resistance	Rg	f=1MHz			5.7		Ω
Switching characteristics ⑤							
Total gate charge	Q_g	$V_{GS}=-10V,$ $V_{DS}=-30V, I_D=-20A$			72	130	nC
Gate-source charge	Q_{gs}				15	29	
Gate-drain charge	Q_{gd}				17	32	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=-30V, R_G=3\Omega$ $R_L=1.5\Omega, V_{GS}=-10V,$			16	30	ns
Turn-on rise time	t_r				18	35	
Turn-off delay time	$t_{d(off)}$				39	78	
Turn-off fall time	t_f				44	87	
Drain-Source Diode Characteristics							
Drain-source diode forward voltage	V_{SD} ④	$V_{GS}=0V, I_S=-20A$				-1.2	V
Continuous drain-source diode forward current	I_S ①					-50	A
Pulsed drain-source diode forward current	I_{SM} ②					-200	A

Notes:

1. $T_C=25^{\circ}\text{C}$ Limited only by maximum temperature allowed.

2. $P_W \leq 10\mu s$, Duty cycles $\leq 1\%$.







3. EAS condition: $V_{DD}=-15V, V_{GS}=-10V, L=0.5\text{mH}, R_g=25\Omega$ Starting $T_J=25^{\circ}\text{C}$.

4. Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.


5. Guaranteed by design, not subject to production.

6. The value of $R_{\theta JA}$ is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_a=25^{\circ}\text{C}$.


Typical Characteristics




Transient Thermal Impedance, Junction-Case



Maximum Safe Operating Area




TO-252-2L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.770	0.025	0.030
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.382	0.406
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250 REF.		0.207 REF.	

TO-252-2L Suggested Pad Layout



Note:


1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

TO-252-2L Tape and Reel

TO-252 Embossed Carrier Tape




Packaging Description:


TO-252 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 25,00 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
TO-252	6.90	10.50	2.70	Ø1.55	1.75	7.50	4.00	8.00	2.00	16.00

TO-252 Tape Leader and Trailer



TO-252 Reel



Dimensions are in millimeter						
Reel Option	D	D1	D2	W1	W2	I
13"Dia	330.00	100.00	Ø21.00	16.40	21.00	Ø13.00

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
2,500 pcs	13inch	2,500 pcs	340×336×29	25,000 pcs	353×346×365	