

Part name	SMD piezo buzzers Passive	Date	2026-09-09
Part number	BUZ-CPT-0918-3.0-4.0	Edition	V2.0
Department		Page	2 / 5


D. TESTING METHOD

Standard Measurement conditions


Temperature: $25 \pm 2^{\circ}\text{C}$ Humidity: 45-65%

Acoustic Characteristics:


The oscillation frequency, current consumption and sound pressure are measured by the measuring instruments shown below



In the measuring test, buzzer is placed as follows:



E. Typical Frequency Response Curve




Part name	SMD piezo buzzers Passive	Date	2026-09-09
Part number	BUZ-CPT-0918-3.0-4.0	Edition	V2.0
Department		Page	3 / 5

F. Soldering Condition

(1)Recommendable reflow soldering condition is as follows

(Reflow soldering is twice)


Note:It is requested that reflow soldering should be executed after heat of product goes down to normal.



Heat resistant line
 (Used when heat resistant reliability test is performed)
 (2)Manual soldering
 Manual soldering temperature 350° C within 5 sec.

	Part name	SMD piezo buzzers Passive	Date	2026-09-09
	Part number	BUZ-CPT-0918-3.0-4.0	Edition	V2.0
	Department		Page	4 / 5

G. RELIABILITY TEST

NO.	ITEM	TEST CONDITION AND REQUIREMENT
1	High Temperature Test (Storage)	After being placed in a chamber with 2°C for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: 10dB.
2	Low Temperature Test (Storage)	After being Placed in a chamber with -4°C for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: 10dB.
3	Humidity Test	After being Placed in a chamber with 90-95% R. 2°C for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: 10dB.
4	Temperature Cycle Test	The part shall be subjected to 5 cycles. One cycle shall be consist of :  Allowable variation of SPL after test: 10dB.
5	Drop Test	Drop on a hard wood board of 4cm thick, any directions ,6 times, at the height of 75cm . Allowable variation of SPL after test: 10dB.
6	Vibration Test	After being applied vibration of amplitude of 1.5mm with 10 to 55 Hz band of vibration frequency to each of 3 perpendicular directions for 2 hours . Allowable variation of SPL after test: 10dB.
7	Solderability Test	Lead terminals are immersed in rosin for 5 seconds and then immersed in solder bath of $+30^{\circ}\text{C}$ for 1 seconds . 90% min. lead terminals shall be wet with solder (Except the edge of terminals).
8	Terminal Strength Pulling Test	The force of 9.8N(1.0kg) is applied to each terminal in axial direction for 10 seconds. No visible damage and cutting off.

TEST CONDITION.

Standard Test Condition	:	a) Temperature : $+5^{\circ}\text{C} \sim +35^{\circ}\text{C}$	b) Humidity : 45-85%	c) Pressure : 860-1060mbar
一般测试条件	:	a) 温度 : $+5^{\circ}\text{C} \sim +35^{\circ}\text{C}$	b) 湿度 : 45-85%	c) 气压 : 860-1060mbar
Judgment Test Condition	:	a) Temperature : $+25 \pm 2^{\circ}\text{C}$	b) Humidity : 60-70%	c) Pressure : 860-1060mbar
争议时测试条件	:	a) 温度 : $+25 \pm 2^{\circ}\text{C}$	b) 湿度 : 60-70%	c) 气压 : 860-1060mbar

Part name	SMD piezo buzzers Passive	Date	2026-09-09
Part number	BUZ-CPT-0918-3.0-4.0	Edition	V2.0
Department		Page	5 / 5

H. PACKING STANDARD

