



JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

PDFNWB3.3×3.3-8L Plastic-Encapsulate MOSFETS

CJAB18SN03 N-Channel Power MOSFET

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
30V	10.5mΩ@10V	18A
	16.5mΩ@4.5V	

DESCRIPTION

The CJAB18SN03 uses shielded gate trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications


FEATURES

- High density cell design for ultra low $R_{DS(ON)}$
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation
- Special process technology for high ESD capability


APPLICATIONS

- High side switch in POL DC/DC converter
- Secondary side synchronous rectifier


MARKING



CJAB18SN03 = Part No.
Solid dot = Pin1 indicator.
XX = Code.



EQUIVALENT CIRCUIT



ABSOLUTE MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D ①	18	A
Pulsed Drain Current	I_{DM} ②	72	A
Single Pulsed Avalanche Energy	E_{AS} ③	20	mJ
Power Dissipation	P_D ①	22	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$ ⑥	83.3	$^{\circ}\text{C/W}$
Thermal Resistance from Junction to Case	$R_{\theta JC}$ ①	5.68	$^{\circ}\text{C/W}$
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55~+150	$^{\circ}\text{C}$

MOSFET ELECTRICAL CHARACTERISTICS

$T_a=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Off characteristics							
Drain-source breakdown voltage	V _{(BR) DSS}	V _{GS} = 0V, I _D =250μA		30			V
Zero gate voltage drain current	I _{DSS}	V _{DS} =24V, V _{GS} =0V	T _J =25 ℃			1.0	μA
			T _J =125 ℃			100	
Gate-body leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V				±100	nA
On characteristics ^④							
Gate-threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA		1.0	1.7	2.5	V
Static drain-source on-sate resistance	R _{DS(on)}	V _{GS} =10V, I _D =10A			10.5	13	mΩ
		V _{GS} =4.5V, I _D =10A			12.5	22	mΩ
Dynamic characteristics ^{④ ⑤}							
Input capacitance	C _{iSS}	V _{DS} =15V,V _{GS} =0V, f =100KHz			330	660	pF
Output capacitance	C _{oss}				150	300	
Reverse transfer capacitance	C _{rSS}				6	12	
Gate resistance	R _g	f =1MHz			10		Ω
Switching characteristics ^{④ ⑤}							
Total gate charge	Q _g	V _{GS} =10V, V _{DS} =20V, I _D =10A			6.0	12	nC
Gate-source charge	Q _{gs}				0.6	1.2	
Gate-drain charge	Q _{gd}				1.5	3.0	
Turn-on delay time	t _{d(on)}	V _{DD} =5V,I _D =10A, V _{GS} =4.5V,R _G =3.3Ω			17.5		ns
Turn-on rise time	t _r				21.3		
Turn-off delay time	t _{d(off)}				48		
Turn-off fall time	t _f				61		
Drain-Source Diode Characteristics							
Drain-source diode forward voltage	V _{SD} ^④	V _{GS} =0V, I _S =10A				1.2	V
Continuous drain-source diode forward current	I _S ^①					18	A
Pulsed drain-source diode forward current	I _{SM} ^②					72	A

Notes:

1. $T_C = 25^{\circ}\text{C}$ Limited only by maximum temperature allowed.

2. $P_W \leq 10\mu s$, Duty cycle $\leq 1\%$.







3. EAS condition: $V_{DD} = 15V, V_{GS} = 10V, L = 0.1mH, R_g = 25\Omega$ Starting $T_J = 25^{\circ}\text{C}$.

4. Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.





5. Guaranteed by design, not subject to production.

6. The value of $R_{\theta JA}$ is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_a = 25^{\circ}\text{C}$.


Typical Characteristics




Typical Characteristics




PDFNWB3.3×3.3-8L PACKAGE OUTLINE DIMENSIONS



Top View
[顶视图]



Bottom View
[背视图]




Side View
[侧视图]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.65	0.90	0.026	0.035
A1	0.15 REF.		0.006 REF.	
A2	0~0.05		0~0.002	
D	2.90	3.20	0.114	0.126
D1	3.00	3.40	0.118	0.134
D2	2.30	2.70	0.091	0.106
E	2.90	3.20	0.114	0.126
E1	3.00	3.40	0.118	0.134
E2	1.60	1.90	0.063	0.075
b	0.20	0.42	0.008	0.017
e	0.65 BSC.		0.026 BSC.	
L	0.20	0.50	0.008	0.020
H	0.32	0.52	0.012	0.020

- Notes:
- 1 Dimensions exclusive of mold gate burrs.
 - 2 Dimensions exclusive of mold flash and cutting burrs.

PDFNWB3.3×3.3-8L Suggested Pad Layout




- Notes:
- 1 Controlling dimension: in millimeters.
 - 2 General tolerance:±0.05mm.
 - 2 The pad layout is for reference purpose only.

NOTICE

JSCJ reservesthe right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein.JSCJ does not assume any liability arising out of the application or use of any product described herein.

PDFNWB3.3×3.3-8L Embossed Carrier Tape




Packaging Description:


PDFNWB3.3×3.3-8L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 5,000 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
PDFNWB3.3×3.3-8L	3.55	3.55	1.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

PDFNWB3.3×3.3-8L Tape Leader and Trailer



PDFNWB3.3×3.3-8L Reel



Dimensions are in millimeter						
Reel Option	D	D1	D2	G	W1	W2
13"Dia	Ø330.00	100.00	13.00	1.90	17.60	12.40

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
5,000 pcs	13 inch	5,000 pcs	340×336×29	50,000 pcs	353×346×365