

SOT-23 Plastic-Encapsulate Transistors

MMBTA43 TRANSISTOR (NPN)

FEATURES


- High Voltage Application
- Telephone Application
- Complementary to MMBTA93

MARKING:ABX

MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)


Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	200	V
V_{CEO}	Collector-Emitter Voltage	200	V
V_{EBO}	Emitter-Base Voltage	5	V
I_{C}	Collector Current	500	mA
P_{C}	Collector Power Dissipation	350	mW
$R_{\theta\text{JA}}$	Thermal Resistance From Junction To Ambient	357	$^{\circ}\text{C/W}$
$T_{\text{J}}, T_{\text{stg}}$	Operation Junction and Storage Temperature Range	$-55 \sim +150$	$^{\circ}\text{C}$

SOT - 23



1. BASE
2. EMITTER
3. COLLECTOR

Equivalent Circuit











ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(\text{BR})\text{CBO}}$	$I_{\text{C}}=0.1\text{mA}, I_{\text{E}}=0$	200			V
Collector-emitter breakdown voltage	$V_{(\text{BR})\text{CEO}}$	$I_{\text{C}}=1\text{mA}, I_{\text{B}}=0$	200			V
Emitter-base breakdown voltage	$V_{(\text{BR})\text{EBO}}$	$I_{\text{E}}=0.1\text{mA}, I_{\text{C}}=0$	5			V
DC current gain	$h_{\text{FE}(1)}^*$	$V_{\text{CE}}=10\text{V}, I_{\text{C}}=10\text{mA}$	40			
	$h_{\text{FE}(2)}^*$	$V_{\text{CE}}=10\text{V}, I_{\text{C}}=1\text{mA}$	40			
	$h_{\text{FE}(3)}^*$	$V_{\text{CE}}=10\text{V}, I_{\text{C}}=30\text{mA}$	40			
Collector-emitter saturation voltage	$V_{\text{CE}(\text{sat})}^*$	$I_{\text{C}}=20\text{mA}, I_{\text{B}}=2\text{mA}$			0.5	V
Base-emitter saturation voltage	$V_{\text{BE}(\text{sat})}^*$	$I_{\text{C}}=20\text{mA}, I_{\text{B}}=2\text{mA}$			0.9	V
Transition frequency	f_{T}	$V_{\text{CE}}=20\text{V}, I_{\text{E}}=10\text{mA}, f=100\text{MHz}$	50			MHz
Collector output capacitance	C_{ob}	$V_{\text{CB}}=20\text{V}, I_{\text{E}}=0, f=1\text{MHz}$			4	pF

*Pulse test: pulse width $\leq 300\mu\text{s}$, duty cycles $\leq 2.0\%$.

Typical Characteristics




SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.05 mm.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

SOT-23 Embossed Carrier Tape




Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	