


Strip Block for Snap-in Mounting with up to 7 IEC Appliance Outlets F

new



See below:

Approvals and Compliances

Description

- Panel mount
- Snap-in version front side (1.2 / 1.5 / 1.7 mm)
- Configurable Strip block from 2 up to 7 outlets type F
- Cord retention for cordsets with V-Lock, Twylock or P-Lock
- Pre-assembled Light Pipe for status indication
- Solder / PCB / QC (4.8 / 6.3 x 0.8) mm

Unique Selling Proposition

- Configurable Bus bar (L, N, PE)
- Optionally with or without light pipes on L or N side
- Color coding in black (grey and white upon request)
- Solder / PCB / QC (4.8 / 6.3 x 0.8 mm)

Characteristics

- Compact solution for intelligent PDU applications
- Suitable for use in equipment according to IEC/UL 62368-1

Other versions on request

- Other panel thicknesses
- Other Light Pipe lengths
- Color coding in White and Grey
- Other terminals on request

Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Approvals](#), [Distributor-Stock-Check](#), [Detailed request for product](#), [Landing Page](#)

The integration of light pipes in the appliance outlet provides status indication in smart PDUs. See PDU Landing Page for more information.

[Power Distribution Units](#)

Technical Data

Ratings IEC	10 A / 250 VAC; 50 Hz
Ratings UL/CSA	15 A / 250 VAC; 60 Hz
Dielectric Strength	> 2 kVAC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz)
Allowable Operation Temperature	-25 °C to 70 °C pin temperature
IP-Protection	front side IP20 acc. to IEC 60529
Protection against electric shock	Suitable for appliances with protection class I acc. to IEC 61140
Terminal	Solder / PCB / QC (4.8 / 6.3 x 0.8) mm
Panel Thickness S	Snap-in (1.2 / 1.5 / 1.7) mm tolerance +0.0/-0.1
Light Pipe Length L	24.5 / 27.5 / 28.5 / 32.7 / 37.4 / 50.0 mm
Material: Housing	Thermoplastic, black / grey / white, UL 94V-0

Appliance inlet/-outlet	F acc. to IEC 60320-3, UL 60320-1 CSA C22.2 no. 60320-1 (for cold conditions) pin- temperature 70 °C, 10 A, Protection Class I
-------------------------	--

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type:

Approval Logo	Certificates	Certification Body	Description
	VDE Approvals	VDE	VDE Certificate Number: 40048640
	UL Approvals	UL	UR File Number: E502078
	CCC Approvals	CCC	CCC Certificate Number: 2018180204005769

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
	Designed according to	IEC 60320-3	Appliance couplers for household and similar general purposes
	Designed according to	UL 60320-1	Standard for Attachment Plugs and Receptacles
	Designed according to	CSA C22.2 no. 60320-1	General Use Receptacles, Attachment Plugs, and Similar Wiring Devices

Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
	Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.


Dimensions [mm]

Socket Length




Number of Outlets	Socket Length (L1) mm	Panel cut-out Length (L2) mm
2	51.2 mm	48.3 mm
3	75.2 mm	72.3 mm
4	99.2 mm	96.3 mm
5	123.2 mm	120.3 mm
6	147.2 mm	144.4 mm
7	171.2 mm	168.4 mm

Max. Hight Socket + Terminal




Terminal Variation	Maximum Height (H) mm
Solder Terminal	31.30 mm
PCB Terminal	34.20 mm
QC 4.8 Terminal	35.20 mm
QC 6.3 Terminal	36.80 mm

Snap-In and Light-Pipes




Lightpipe length (L) mm	Panel thickness Snap-In (S) mm
27.5 mm	1.20 mm
32.7 mm	1.50 mm
37.4 mm	1.70 mm
50.0 mm	
28.5 mm	
24.5 mm	


Drilling diagram for PCB terminals: All bussed [mm]




Drilling diagram for PCB terminals: L individua andl N/PE bussed [mm]



Drilling diagram for PCB terminals: L/N individual and PE bussed [mm]



Drilling diagram for PCB terminals: L/N/PE individual [mm]



Number of Outlets	Drilling diagram for bussed type PCB terminal Length (L3) mm	Drilling diagram for individual type PCB terminal Length (L4) mm
2	32.74 mm	24.4 mm
3	56.74 mm	24.4 mm
4	80.74 mm	24.4 mm
5	104.74 mm	24.4 mm
6	128.74 mm	24.4 mm
7	152.74 mm	24.4 mm

Variants

Outlets	Mounting	Light pipe L side	Light pipe N side	Color	Hard-Wired Bus	Position of Terminal on bus	Terminal type	Order Number
2 - ganged outlet	snap-in 1.7 mm	28.5mm	28.5mm	black	L/N individual, PE bussed	Bussed one terminal on bottom side	PCB	3-135-281
2 - ganged outlet	snap-in 1.7 mm	w/o hole	28.5mm	black	L/N individual, PE bussed	Bussed one terminal on bottom side	PCB	3-135-283
2 - ganged outlet	snap-in 1.7 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	PCB	3-135-280
2 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-277
2 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	white	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-278
2 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	QC 4.8 x 0.8	3-138-452
2 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with one terminal on top side	QC 6.3 x 0.8	3-149-674
2 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with terminals on both sides	solder terminals	3-135-157
2 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	solder terminals	3-124-296
3 - ganged outlet	snap-in 1.5 mm	27.5mm	27.5mm	black	N/PE bussed - L individual	Bussed one terminal on bottom side	PCB	3-124-314
3 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	black	L/N/PE bussed	Bussed with terminals on both sides	QC 4.8 x 0.8	3-157-022
3 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-586
3 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	white	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-539
3 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with one terminal on top side	QC 6.3 x 0.8	3-149-673
3 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with one terminal on top side	solder terminals	3-104-399
3 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	solder terminals	3-124-302
3 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with terminals on both sides	solder terminals	3-135-537
4 - ganged outlet	snap-in 1.5 mm	27.5mm	27.5mm	black	N/PE bussed - L individual	Bussed with terminals on both sides	PCB	3-154-756
4 - ganged outlet	snap-in 1.5 mm	27.5mm	27.5mm	black	N/PE bussed - L individual	Bussed one terminal on bottom side	PCB	3-124-315
4 - ganged outlet	snap-in 1.5 mm	w/o hole	27.5mm	black	N/PE bussed - L individual	Bussed with one terminal on top side	PCB	3-104-412
4 - ganged outlet	snap-in 1.5 mm	w/ hole	w/ hole	black	L/N/PE individual, not bussed	All terminals individual	PCB	3-104-370
4 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	PCB	3-144-843
4 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-540
4 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	white	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-541
4 - ganged outlet	snap-in 1.5 mm	27.5mm	27.5mm	white	L/N/PE bussed	Bussed with one terminal on top side	QC 6.3 x 0.8	3-128-802
4 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with one terminal on top side	QC 6.3 x 0.8	3-146-319
4 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with one terminal on top side	solder terminals	3-104-400
4 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with terminals on both sides	solder terminals	3-104-404
4 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	solder terminals	3-124-303
5 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-292
5 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	white	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-293
5 - ganged outlet	snap-in 1.7 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with one terminal on top side	QC 4.8 x 0.8	3-164-170

Outlets	Mounting	Light pipe L side	Light pipe N side	Color	Hard-Wired Bus	Position of Terminal on bus	Terminal type	Order Number
5 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-284
5 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	solder terminals	3-124-304
6 - ganged outlet	snap-in 1.5 mm	27.5mm	27.5mm	black	N individual, L/PE bussed	Bussed with one terminal on top side	PCB	3-120-308
6 - ganged outlet	snap-in 1.5 mm	27.5mm	27.5mm	black	L/N individual, PE bussed	Bussed with one terminal on top side	PCB	3-120-309
6 - ganged outlet	snap-in 1.7 mm	27.5mm	27.5mm	black	L/N individual, PE bussed	Bussed one terminal on bottom side	PCB	3-128-805
6 - ganged outlet	snap-in 1.5 mm	27.5mm	27.5mm	black	N/PE bussed - L individual	Bussed one terminal on bottom side	PCB	3-124-317
6 - ganged outlet	snap-in 1.5 mm	27.5mm	27.5mm	black	L/N individual, PE bussed	Bussed one terminal on bottom side	PCB	3-124-308
6 - ganged outlet	snap-in 1.7 mm	28.5mm	28.5mm	black	L/N individual, PE bussed	Bussed one terminal on bottom side	PCB	3-129-643
6 - ganged outlet	snap-in 1.7 mm	w/o hole	28.5mm	black	L/N individual, PE bussed	Bussed one terminal on bottom side	PCB	3-129-644
6 - ganged outlet	snap-in 1.5 mm	w/ hole	w/ hole	black	L/N/PE individual, not bussed	All terminals individual	PCB	3-104-371
6 - ganged outlet	snap-in 1.7 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	PCB	3-127-128
6 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	PCB	3-144-844
6 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-552
6 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	white	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-553
6 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with one terminal on top side	QC 6.3 x 0.8	3-149-675
6 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with terminals on both sides	QC 6.3 x 0.8	3-120-305
6 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with one terminal on top side	solder terminals	3-104-402
6 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with terminals on both sides	solder terminals	3-104-405
6 - ganged outlet	snap-in 1.7 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed with terminals on both sides	solder terminals	3-128-806
6 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	solder terminals	3-124-305
7 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-295
7 - ganged outlet	snap-in 1.5 mm	27.5mm	w/o hole	white	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-296
7 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	N/PE bussed - L individual	Bussed with terminals on both sides	QC 4.8 x 0.8	3-135-294
7 - ganged outlet	snap-in 1.5 mm	w/o hole	w/o hole	black	L/N/PE bussed	Bussed one terminal on bottom side	solder terminals	3-124-306

Availability for all products can be searched real-time: <https://www.schurter.com/en/info-center/support-tools/stock-check-distributors>

Mating Inlets/Plugs

Category / Description

Plug Overview complete



4732, Mounting: Power Cord, Plug: IEC E, Cable	4732
4735, Mounting: Power Cord, Plug: IEC E, Cable	4735
9009, Mounting: Plug: IEC E, Screw clamps	9009
4733, Mounting: Power Cord, Plug: IEC E, Cable	4733
4736, Mounting: Power Cord, Plug: IEC E, Cable	4736

...