



**SOT-363 Plastic-Encapsulate Transistors****MMDT2907A** DUAL TRANSISTOR (PNP+PNP)**FEATURE**

- Complementary NPN Type available MMDT2222A

MARKING: K2F**MAXIMUM RATINGS** ($T_a=25^{\circ}\text{C}$ unless otherwise noted)


Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	-60	V
V_{CEO}	Collector-Emitter Voltage	-60	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_{C}	Collector Current -Continuous	-600	mA
P_{C}	Collector Power Dissipation	200	mW
$T_{\text{J}}, T_{\text{stg}}$	Operation Junction and Storage Temperature Range	-55~+150	$^{\circ}\text{C}$

**ELECTRICAL CHARACTERISTICS** ($T_a=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Max	Unit
Collector-base breakdown voltage	$V_{(\text{BR})\text{CBO}}$	$I_{\text{C}} = -10\mu\text{A}, I_{\text{E}} = 0$	-60		V
Collector-emitter breakdown voltage	$V_{(\text{BR})\text{CEO}}$	$I_{\text{C}} = -10\text{mA}, I_{\text{B}} = 0$	-60		V
Emitter-base breakdown voltage	$V_{(\text{BR})\text{EBO}}$	$I_{\text{E}} = -10\mu\text{A}, I_{\text{C}} = 0$	-5		V
Collector cut-off current	I_{CBO}	$V_{\text{CB}} = -50\text{V}, I_{\text{E}} = 0$		-10	nA
Collector cut-off current	I_{CEX}	$V_{\text{CE}} = -30\text{V}, V_{\text{EB(off)}} = -0.5\text{V}$		-50	nA
Emitter cut-off current	I_{EBO}	$V_{\text{EB}} = -5\text{V}, I_{\text{C}} = 0$		-10	nA
DC current gain	$h_{\text{FE}(1)}$	$V_{\text{CE}} = -10\text{V}, I_{\text{C}} = -0.1\text{mA}$	75		
	$h_{\text{FE}(2)}$	$V_{\text{CE}} = -10\text{V}, I_{\text{C}} = -1\text{mA}$	100		
	$h_{\text{FE}(3)}$	$V_{\text{CE}} = -10\text{V}, I_{\text{C}} = -10\text{mA}$	100		
	$h_{\text{FE}(4)}$	$V_{\text{CE}} = -10\text{V}, I_{\text{C}} = -150\text{mA}$	100	300	
	$h_{\text{FE}(5)}$	$V_{\text{CE}} = -10\text{V}, I_{\text{C}} = -500\text{mA}$	50		
Collector-emitter saturation voltage	$V_{\text{CE(sat)1}}$	$I_{\text{C}} = -150\text{mA}, I_{\text{B}} = -15\text{mA}$		-0.4	V
	$V_{\text{CE(sat)2}}$	$I_{\text{C}} = -500\text{mA}, I_{\text{B}} = -50\text{mA}$		-1.6	V
Base-emitter saturation voltage	$V_{\text{BE(sat)1}}$	$I_{\text{C}} = -150\text{mA}, I_{\text{B}} = -15\text{mA}$		-1.3	V
	$V_{\text{BE(sat)2}}$	$I_{\text{C}} = -500\text{mA}, I_{\text{B}} = -50\text{mA}$		-2.6	V
Transition frequency	f_{T}	$V_{\text{CE}} = -20\text{V}, I_{\text{C}} = -50\text{mA}, f = 100\text{MHz}$	200		MHz
Output Capacitance	C_{ob}	$V_{\text{CB}} = -10\text{V}, I_{\text{E}} = 0, f = 1\text{MHz}$		8	pF
Input Capacitance	C_{ib}	$V_{\text{EB}} = -2\text{V}, I_{\text{C}} = 0, f = 1\text{MHz}$		30	pF
Delay time	t_{d}	$V_{\text{CC}} = -30\text{V}, I_{\text{C}} = -150\text{mA}, I_{\text{B1}} = -15\text{mA}$		10	ns
Rise time	t_{r}			40	ns
Storage time	t_{s}	$V_{\text{CC}} = -6\text{V}, I_{\text{C}} = -150\text{mA}, I_{\text{B1}} = I_{\text{B2}} = -15\text{mA}$		225	ns
Fall time	t_{f}			60	ns

Typical Characteristics


Static Characteristic




h_{FE} — I_C




V_{CEsat} — I_C




V_{BEsat} — I_C




I_C — V_{BE}




C_{ob}/C_{ib} — V_{CB}/V_{EB}



P_c — T_a



SOT-363 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.100	0.150	0.004	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.400	0.085	0.094
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

SOT-363 Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.


SOT-363 Embossed Carrier Tape




Packaging Description:
SOT-363 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-363	2.25	2.55	1.20	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-363 Tape Leader and Trailer



SOT-363 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	